

# TEK22 series

## Dual Motor Desk Frame

### General Features


Max. load	Up to 200kg*
Constant speed	3-Stage Column: Up to 40mm/s* 2-Stage Column: Up to 33mm/s*
Weight of package	33~40Kg*
Standby power	< 0.1W
Accessories	USB Chargers (TFA1/TFA3), Anti-Collision Sensor (TCS1), Wireless Chargers (TWC)

Multiple column and control options

High strength and stability – Steel construction

Pre-assembled frame kit – Significantly reduces installation time

\*It varies upon the selection of components.




### Color (RAL Classic)



\*For more color options, please consult your sales representative.



**Dimension**



**Frame & Work Surface**

Frame dimensions (mm)	Recommended work surface dimensions (mm)	
Width (mm)	Width (mm)	Depth (mm)
1050~1700	1100~1800	700~1000

**Hight Range**

Column type	Frame height (mm)	Stroke (mm)
3-Stage	630~1280	650
3-Stage (M)	600~1260	660
3-Stage (S)	560~1220	660
2-Stage	680~1180	500

TL Model

• 2-Stage



TL13S  
Square  
70 x 70 mm



TL15H  
Rectangular  
80 x 60 mm



TL30S  
Rectangular  
90 x 60 mm




TL32S  
Rectangular  
83 x 53 mm



TL32SR  
Rectangular  
83 x 53 mm

• 3-Stage



TL4S  
Square  
70 x 70 mm




TL10H  
Rectangular  
80 x 60 mm



TL31S  
Rectangular  
90 x 60 mm



TL33S  
Rectangular  
83 x 53 mm




TL33SR  
Rectangular  
83 x 53 mm

**End Pipe**




Style A  
(Fixation holes for tabletop)



Style A1  
( Fixation holes for tabletop)




Style B, C for C-leg  
(Fixation holes for tabletop)




Foot




Style A




Style B




Style C



Style D



Style E



Style F



Style G



Style H



Style J



Foot (mm)



Code	Style	Frame type	Length (mm)
<b>0</b>	-	Without	-
<b>AT1</b>	A	T	750
<b>AT2</b>	A	T	680
<b>AT4</b>	A	T	600
<b>AT6</b>	A	T	550
<b>AT7</b>	A	T	350
<b>AC1</b>	A	C	750
<b>AC4</b>	A	C	600
<b>AC5</b>	A	C	580
<b>BT1</b>	B	T	750
<b>BT2</b>	B	T	680
<b>BT6</b>	B	T	550
<b>BC1</b>	B	C	750
<b>BC2</b>	B	C	680
<b>BC5</b>	B	C	580
<b>CT1</b>	C	T	750
<b>CT4</b>	C	T	600
<b>CT6</b>	C	T	550
<b>DT1</b>	D	T	750
<b>DT6</b>	D	T	550
<b>ET1</b>	E	T	750
<b>FT2</b>	F	T	680
<b>HT2</b>	H	T	680
<b>JC3</b>	J	C	650

Hand Control



1 = TH37



2 = TFH8



3 = TDH1



4 = TDH2



5 = TDH3




6 = TDH4



7 = TDH5



8 = TDH6



9 = TFH13



B = TH14



C = TFH21



D = TDH8P



E = TDH8



F = TDH8D



G = TDH11P



H = TDH12P



K = TDH16



L = TDH6PR



M = TDH5PR



N = TDH13P



P = TDH15



Q = TDH18P



R = TDH17



S = TDH20P

### Hand Control



T = TDH9P



U = TDH27P



V = TDH24P

### Accessories (optional)



TCS1

TCS1 is a collision sensor based on t-touch technology which does not require any additional hardware upgrades.



TFA1

A charger with 2 USB ports. Can be mounted on the table top.



TFA3

A charger with 2 USB ports. Can be mounted to the desk front side.



TWC

Designed for wireless charging of mobile devices. Can be mounted on the table top.

# TEK22 Ordering Key

## TEK22

Version: 20220119-G

<b>TL Model</b>	004S = TL4S	030S = TL30S	032S = TL32S	33SR = TL33SR	010H = TL10H	009K = TL9K
<a href="#">See page 3</a>	013S = TL13S	031S = TL31S	033S = TL33S	32SR = TL32SR	015H = TL15H	014K = TL14K
	Note: *TL13(S) & TL14 & TL15 & TL26 & TL28 & TL29 & TL13S & TL30S & TL32S & TL32SR & TL15H & TL14K are 2 stages columns					
<b>Foot (mm)</b>	<a href="#">See page 5-6</a>					
<b>Color</b>	1 = Black (RAL 9005)		3 = White (RAL 9016)		6 = Matte Black (RAL 7021)	
	2 = Grey (RAL 9006)		4 = Special grey (RAL 9022)		7 = Graphite grey (RAL 7024)	
<b>TC Model</b>	0 = Without		3 = TC15S			
<b>Hand Control</b>	<a href="#">See page 7-8</a>					
<b>End Pipe (mm)</b>	1 = Style A, fixation holes, fixed with outer pipe, E1 & E2: 550			3 = Style A1, fixation holes, fixed with motor house, E1 & E2: 360		
<a href="#">See page 4</a>	2 = Style A1, fixation holes, fixed with motor house, E1 & E2: 550			7 = Style B, fixation holes, fixed with outer pipe, E1 & E2: 580, for C-leg		
<b>Desk Frame (mm)</b>	1 = Normal, outer pipe 25*40, W: 1050-1700					
<b>Assembly Manual</b>	0 = Without			3 = Chinese, No logo, Black / White printing		
	C = Chinese, TiMOTION logo, Black / White printing			4 = English, No logo, Black / White printing		
	E = English, TiMOTION logo, Black / White printing			5 = Chinese, No logo, colour printing		
	1 = Chinese, TiMOTION logo, colour printing			6 = English, No logo, colour printing		
	2 = English, TiMOTION logo, colour printing					

## Terms of Use

The user is responsible for determining the suitability of TiMOTION products for a specific application. TiMOTION products are subject to change without prior notice.